



UK: Declaration of Performance (DOP)

Shape 1, Shape 2, Shape 1 Stone, Shape 2 Stone

Product type		Fritstående ovn	
Type, batch or serial number		Shape 1, Shape 2, Shape 1 Stone, Shape 2 Stone	
Intended use of the product		This stove is designed for solid fuel and intermittent burning. Without hot water supply.	
Name and Address of the manufacturer		Varde Ovne A/S Pottemagervej 1 7100 Vejle, Danmark	
AVCP		System 3	
Approval place Notified body no. Test report no.		RRF, Im Lipperfeld 34b, D-46047 Oberhausen NB-No 1625 Rapport nr. RRF- 40 14 3655, RRF- AU 14 3655 Teknologisk Institut, Kongsvang Alle 29, DK-8000 Aarhus C NB-No 1427, Rapport nr. 300-ELAB-1281-NS	
Declared performance			
Harmonized technical specification		EN 13240:2001/A2:2004/AC:2007 Art. 15a B-VG, NS-3058	
Seasonal Space Efficiency (EEI) EU 2015/1186		107	
Essential characteristics		Performance	
Fire safety			
Reaction to fire		A1	
Distance to combustible materials Minimum distances, in mm		Rear = 100 Sides = 250 Front = 800	
Fuel types		Primary: Wood, moisture content ≤ 25% Secondary: Pressed wood briquettes, moisture content ≤ 12% Air regulation: Manuel stepless	
Emission of combustion products CO OGC Dust NOX	Art 15-A 566 mg/MJ 38 mg/MJ 15 mg/MJ 91 mg/MJ	EN 13240 13% O ₂ 875 mg/Nm ³ – 0,07 % 64 mg/Nm ³ 23 mg/Nm ³ 139 mg/Nm ³	NS 3058 / NS 3059 Total 3,16 g/kg – max. 3,69 g/kg
Surface temperature		OK	
Electrical safety		–	
Clean ability		OK	
Maximum water operating pressure		–	
Flue gas temperature at nominal heat output		285 °C	
Mechanical resistance (to carry a chimney/flue)		OK	
Thermal output			
Normal heat output		5,4 kW	
Room heating output		5,4 kW	
Water heating output		–	
Energy efficiency	80 %	80 %	
Annual efficiency	72 %	72 %	

Date of issue: 17. November, 2017.

Udført af: Annette Blendstrup

Godkendt af: Michael Verman

Dato/revision: 16.02.2022 / 9

Signed on behalf of the manufacturer

Michael Verman, CEO

